ASIA PACIFIC INDUSTRY GROUP CO., LIMITED
Tel +0086-551-64687285
Email sales@boppfilmsales.com
www.boppfilmsales.com · www.apigcl.com

BOPP Adhesive Tape Jumbo Rolls - Quality
BOPP 薄膜 — 检测数据

Document No. 文件编号	Revision 版本	Issue date 签发日期	Document type 文件类型
APIG-COC-TAPE-2026	**Rev. 2.0**	**2026-11-09**	**Test Data / 检测数据**

1 • DOCUMENT INFORMATION 文档信息

Item 项目	Description 说明
Document type 文件类型	Test Data / 检测数据
Subject 主题	BOPP Adhesive Tape Jumbo Rolls - Quality Certificate
Specification basis 规格依据	APIG product specification 亚太工业集团产品规格
Issue 签发	2026-11-09 · Rev. 2.0
Language 语言	Bilingual headings — English / 中文

2 • TECHNICAL CONTENT 技术内容

QUALITY CERTIFICATE BOPP self-adhesive packaging tape is composed of biaxial-oriented polypropylene (BOPP) film and adhesive covering based on Acrylic polymer. This BOPP tape supplied in jumbo rolls is used for production of narrower BOPP tape rolls for sealing of cartons and other purposes. The BOPP tape is available clear, brown, yellowish and colored. 36, 38, 40, 43, 45, 47, 49, 50, 59 BOPP PACKING TAPE JUMBO ROLL’ S Roll’ s width, mm 1280±20 1280±20 1280±20 1280±20 1280±20 Roll’ s length, m 4000±200 4000±200 4000±200 4000±200 4000±200 Total Thickness of tape, mic 36 38 40 43 45 BOPP Film Thickness, mic 23 23 23 23 25 Acrylic polymer covering thickness, mic 13 15 17 20 20 Color of tape WHITE CLEAR Type of adhesive Water base Water base Water base Water base Water base Tensile strength 12kg/mm2, 70N/2.5CM. 13kg/mm2, 70N/2.5CM. 14kg/mm2, 70N/2.5CM. 14.5kg/mm2, 80N/2.5CM. 15kg/mm2 75N/2.5CM., 180° peel adhesion 450g/in, ≥ 4.6N/2.5 CM 450g/in, ≥ 5.0N/2.5 CM 450g/in, ≥ 5.4N/2.5 CM 450g/in, ≥ 6. 0N/2.5 CM 450g/in, ≥ 6.4N/2.5 CM Temperature resistance 115 115 115 115 115 Temperature mode of application -60&+80 -60&+80 -60&+80 -60&+80 -60&+80 Elongation at break 100% 105% 110% 115% 120% Test temperature -10 -10 -10 -10 -10 Test humidity ≥120% ≥130% ≥150% ≥170% ≥180% Initial tack (14#) ≥10 ≥12 ≥14 ≥16.5 ≥18.5 Holding power >24 hrs HOUR/2.5CM >24 hrs HOUR/2.5CM >24 hrs HOUR/2.5CM >24 hrs HOUR/2.5CM >24 hrs HOUR/2.5CM Eastern Communication · QUALITY CERTIFICATE BOPP self-adhesive packaging tape is composed of biaxial-oriented polypropylene (BOPP) film and adhesive covering based on Acrylic polymer. This BOPP tape supplied in jumbo rolls is used for production of narrower BOPP tape rolls for sealing of cartons and other purposes. The BOPP tape is available clear, brown, yellowish and colored. 36, 38, 40, 43, 45, 47, 49, 50, 59 BOPP PACKING TAPE JUMBO ROLL’ S Roll’ s width, mm 1280±20 1280±20 1280±20 1280±20 Roll’ s length, m 4000±200 4000±200 4000±200 3300±150 Total Thickness of tape, mic 47 49 50 60(59) BOPP Film Thickness, mic 25 28 28 37 Acrylic polymer covering thickness, mic 22 21 22 22 Color of tape WHITE CLEAR yellowish Type of adhesive Water base Water base Water base Water base Tensile strength 15.5kg/mm2,70N/2.5CM. 16kg/mm2,70N/2.5CM. 16kg/mm2, 80N/2.5CM. 180° peel adhesion 450g/in, ≥ 6.8N/2.5 CM 450g/in, ≥ 7.2N/2.5 CM 450g/in, ≥ 7.2N/2.5 CM 450g/in, ≥ 9.2N/2.5 CM Temperature resistance 115 115 115 115 Temperature mode of application -60&+80 -60&+80 -60&+80 -60&+80 Elongation at break 125% 130% 130% 160% Test temperature -10 -10 -10 -10 Test humidity ≥190% ≥200% ≥200% ≥250% Initial tack (14#) ≥20 ≥20 ≥22 ≥22 Holding power >24 hrs HOUR/2.5CM >24 hrs HOUR/2.5CM >24 hrs HOUR/2.5CM >24 hrs HOUR/2.5CM Eastern Communication ·

以下数据为本产品技术规格，随货签发检验记录。

3 • NOTES 说明

This document states the standard specification of the product. Values apply to the grades listed here; the tolerance range agreed in the order confirmation and the technical agreement prevails for any specific order. Batch test records are issued with the goods on request.