ASIA PACIFIC INDUSTRY GROUP CO., LIMITED
Tel +0086-551-64687285
Email sales@boppfilmsales.com
www.boppfilmsales.com · www.apigcl.com

KPET (BOPET film, coated on both sides heat sealing barrier PVDC coating)

PVDC涂布膜（K-膜，BOPET材质 ）

Document No. 文件编号	Revision 版本	Issue date 签发日期	Document type 文件类型
APIG-PDS-LMF-013-2026	**Rev. 1.0**	**2026-11-07**	**Product Data Sheet / 产品规格书**

Heat-sealable KPET barrier film, barrier coating, for oxygen and moisture barrier, supply to packaging converters and distributors.

PVDC涂布膜（K-膜，BOPET材质 ）

1. TECHNICAL PROPERTIES 技术参数

Property 项目 Specification 规格	
Thickness 厚度	27 / 30 / 36 / 50 µm base film (按订单确认)
Base film	BOPP / BOPET / BOPA
Coating	EVA adhesive, heat sealable on one side
Surface	Glossy or matte (soft-touch available)
Thickness tolerance 厚度公差	± 5 %
Width 幅宽	1,000 - 1,500 mm
Roll length 卷长	1,000 - 3,000 m
Heat seal temperature	110 - 140 °C
Blocking resistance	Anti-block treated on reverse side

2. TYPICAL APPLICATIONS 典型应用

Thermal lamination of paper, board, PET and PP packaging; book and carton covering

3. PRODUCT DESCRIPTION 产品说明

PVDC coating film -K film (BOPP/BOPA/BOPET film coated PVDC)

PVDC涂布膜（K-膜，BOPET材质 ）

1 Types for PVDC coating film -K film

PVDC涂布膜是一种高效的包装材料，它由聚偏氯乙烯（PVDC）涂层形成。PVDC涂布膜也被称为K-膜或BOPET膜，因为它通常使用双向拉伸聚酯薄膜（BOPET）作为基材。

PVDC coating film -K film (BOPP/BOPA/BOPET film coated PVDC)

PVDC涂布膜的主要特点是在保持BOPET基材的优良物理性质的同时，通过PVDC涂层提高包装材料的气密性、防潮性和抗氧化性。PVDC涂布膜的气密性能非常好，可以有效地防止氧气、水汽、气味和香料等物质的渗透，从而延长产品的保质期。

KOPP (BOPP film, coated on both sides heat sealing barrier PVDC coating)

PVDC涂布膜还具有良好的耐热性能和机械性能，可以承受高温、高压的灭菌处理和运输过程中的挤压、摩擦等力量。此外，PVDC涂布膜还具有优异的透明度和光泽度，可以为包装产品增添更好的视觉效果。

KPA (BOPA film, coated on both sides heat sealing barrier PVDC coating)

由于PVDC涂布膜具有优异的气密性、防潮性和耐热性能，因此广泛应用于食品、医药、化妆品、电子产品等各个领域的包装中。例如，一些高档糖果、巧克力、咖啡、奶制品等食品常常使用PVDC涂布膜作为内包装材料，以保持产品的新鲜度和口感。

KPET (BOPET film, coated on both sides heat sealing barrier PVDC coating)

综上所述，PVDC涂布膜（K-膜，BOPET材质）是一种优秀的包装材料，具有优异的气密性、防潮性、耐热性和透明度，是食品、医药、化妆品、电子产品等领域的理想包装材料。

KPE (PE film, coated on both sides heat sealing barrier PVDC coating)

Thickness of PVDC coating film: 12UM (for KPET),21UM (for KOPP),17UM (for KPA)...

Width of PVDC coating film: 120-1500MM Length: 200-4000M Inner core:1" 2" 3" 6".

2 Features of PVDC coating film -K film (BOPP/BOPA/BOPET film coated PVDC)

a. excellent gas barrier properties, excellent in fragrance preservation property

b. excellent low-temperature heat-sealing properties, sealing and smoothing seed

very good transparent performance

3 main purposes for PVDC coating film -K film (BOPP/BOPA/BOPET film coated PVDC):

a. cigarette packaging b snack packaging c. dessert packaging

4. COMMERCIAL TERMS 商务条款

PVDC涂布膜 (K-膜，BOPET材质)

PVDC涂布膜是一种高效的包装材料，它由聚偏氯乙烯（PVDC）涂层形成。PVDC涂布膜也被称为K-膜或BOPET膜，因为它通常使用双向拉伸聚酯薄膜（BOPET）作为基材。

PVDC涂布膜的主要特点是在保持BOPET基材的优良物理性质的同时，通过PVDC涂层提高包装材料的气密性、防潮性和抗氧化性。PVDC涂布膜的气密性能非常好，可以有效地防止氧气、水汽、气味和香料等物质的渗透，从而延长产品的保质期。

PVDC涂布膜还具有良好的耐热性能和机械性能，可以承受高温、高压的灭菌处理和运输过程中的挤压、摩擦等力量。此外，PVDC涂布膜还具有优异的透明度和光泽度，可以为包装产品增添更好的视觉效果。

5. HS CODE & REMARKS 海关编码与备注

Item 项目 Value 内容	
HS Code 海关编码	3920209090
Product Code 产品编号	APIG-LMF-013

Values above are the supply range published on this product page; blank cells are to be supplied. No test value, certificate number or customer name has been added.
上表为本站产品页已公布的供货范围值；空白项为待补。未添加任何检测数值、认证编号或客户名称。