ASIA PACIFIC INDUSTRY GROUP CO., LIMITED
Tel +0086-551-64687285
Email sales@boppfilmsales.com
www.boppfilmsales.com · www.apigcl.com

Asia Pacific -502 Super Glue MSDS

PE 薄膜 — 材料安全数据表

Document No. 文件编号	Revision 版本	Issue date 签发日期	Document type 文件类型
APIG-RD-20180921134753-2026	**Rev. 2.0**	**2026-11-09**	**Material Safety Data Sheet / / 技术数据表**

1 • DOCUMENT INFORMATION 文档信息

Item 项目	Description 说明
Document type 文件类型	Material Safety Data Sheet / 材料安全数据表
Subject 主题	Asia Pacific -502 Super Glue MSDS
Specification basis 规格依据	APIG product specification 亚太工业集团产品规格
Issue 签发	2026-11-09 · Rev. 2.0
Language 语言	Bilingual headings — English / 中文

2 • TECHNICAL CONTENT 技术内容

1 502 SUPER GLUE MSDS 502 胶水物质安全资料表 Part 1：Name of Product Chinese name：502 胶 English Name：502 Super Glue; Cyanoacrylate Adhesive Part 2: Ingredients Identification Information CAS No. ECA 90-100% 7085-85-0 PMMA 0-9.5% 9011-14-7 0-0.5% 123-31-9 Part 3: Hazards Identification Hazards classification: Not hazardous material Way of approach: Inhalation, Ingestion, Skin contact Health hazards: Contacting skin may cause irritation Environment hazards: None Risk of explosion: Flammable Part 4: First aid measures: Skin contact: Wash off immediately with plenty of soap and water，if any titillation or inflammation, seek medical advice; Eye contact: Rinse immediately with plenty off water for at least 15 minutes, after that seek medical advice; Inhalation: If feel upset, move to fresh air and seek medical advice Ingestion: Rinse mouth with water, give water to dilute stomach contents, then Get prompt medical attention. Part 5: Fire fighting measures: Risk: Irritation, flammable, burning will produce noxious gas Generation of burning: CO\CO2\ Nitrogen oxides Fire fighting: Cut off fire source and use fire extinguisher in the wind direction Available fire extinguisher: Fire foam，fire powder, CO2, dry sands Part 6: Accidental leak measures: 2 Emergency treatment: Remove or shut off ignition source, prepare fire-fighting equipment; and use rag, gauze, sands to absorb leaked liquid to recycle into container; must wear PPE and keep adequate ventilation inside the room. Part 7: Handling & storage: Caution for handling: Operator should be trained before operation and follow SOP strictly, suggest operator to wear apron, avoid eye contact, skin contact directly and inhalation; avoid exposing under this condition for long and continuous period. Caution for storage: Store in cool, dry and good ventilation area away from spark or fire. Part 8: Exposure controls & personal protection: Respiration protection: Under conditions of frequent use or heavy exposure, mask will be needed Eye protection: Wear chemical goggles Body protection: Wear normal uniform Hand protection: Wear gloves Others: Prohibited to smoking, eating and drinking at working place. Wash polluted clothes after working. Part 9: Physical & Chemical properties: Appearance: Colorless transparent liquid with irritating odor Boiling point(℃): 54～56 Relative density (water=1): Not available Relative vapour density (air=1): Not available Flash point (℃): 75 Molecular formula: C6H7NO2 Solubility in water: Insoluble Usage: Used for sticking ceramic, rubber, glass, jewelry, plastic, furniture, advertisement board etc Part 10: Stability & Reactivity: Stability: Stable under normal storage conditions Prohibit to add: Oxidizer, reducer, water, amic, carbinol , alkali metals and eatable chemicals Conditions to Avoid: Light Incompatibility: Will polymerize when meet water Decomposition Products: CO\CO2\ Nitrogen oxides Part 11: Toxicological Information: 3 Acute toxicity: None Chronic: None Irritation: May irritate eyes, cause tear, irritating skin or

以下数据为本产品技术规格，随货签发检验记录。

respiration system Mutation: / Monstrosity: / Cancerous: / Part 12: Disposal Information: Property of waste: Kind of organic cyanide Disposal method: Burn in closed tank or Consign the disposal to the specialist of industrial waste after clarifying that the goods are flammable waste. Part 13: Transport Information: Packing type: None Packing method: None Transport regulation: Make sure of no leakage; prohibit putting bottom up, drop, damage, and binding tightly during transportation

3 • NOTES 说明

地址 ADD.: No.3399, Luzhou Ave., Baohe Dist., Hefei, Anhui 230051, China | 安徽省合肥市包河区庐州大道3399号
传真 Fax: +0086-551-64683490 **营业执照注册号 Business License Reg. No.:** 91340100575703313N
海关注册编码 Customs Reg. Code: 3401961393

ASIA PACIFIC INDUSTRY GROUP CO., LIMITED
Tel +0086-551-64687285
Email sales@boppfilmsales.com
www.boppfilmsales.com · www.apigcl.com

This document states the standard specification of the product. Values apply to the grades listed here; the tolerance range agreed in the order confirmation and the technical agreement prevails for any specific order. Batch test records are issued with the goods on request.