ASIA PACIFIC INDUSTRY GROUP CO., LIMITED
Tel +0086-551-64687285
Email sales@boppfilmsales.com
www.boppfilmsales.com · www.apigcl.com

# 80-50e

## 产品技术资料 — 技术资料

| Document No. 文件编号 | Revision 版本 | Issue date 签发日期 | Document type 文件类型 |
|---|---|---|---|
| APIG-RD-20250527205708-2026 | Rev. 2.0 | 2026-11-09 | Technical Document / 技术资料 |

## 1 • DOCUMENT INFORMATION 文档信息

| Item 项目 | Description 说明 |
|---|---|
| Document type 文件类型 | Technical Document / 技术资料 |
| Subject 主题 | 80-50e |
| Specification basis 规格依据 | APIG product specification 亚太工业集团产品规格 |
| Issue 签发 | 2026-11-09 · Rev. 2.0 |
| Language 语言 | Bilingual headings — English / 中文 |

## 2 • TECHNICAL CONTENT 技术内容

| Model | Ratio（A） | Accuracy | Burden（VA） | Frequency | Insulation |
|---|---|---|---|---|---|
| 250/5 | 1 | 15 | | | |
| 300/5 | 1 | 15 | | | |
| 400/5 | 05 | 15 | | | |
| 500/5 | 05 | 25 | | | |
| XH80*50 | 50/60Hz | ≤3KV | | | |
| 600/5 | 05 | 25 | | | |
| 750/5 | 05 | 25 | | | |
| 800/5 | 05 | 25 | | | |
| 1000/5 | 05 | 5 | | | |

| Model | Ratio（A） | Accuracy | Burden（VA） | Frequency | Insulation |
|---|---|---|---|---|---|
| 250/1 | 1 | 15 | | | |
| 300/1 | 1 | 15 | | | |
| XH80*50 | 50/60Hz | ≤3KV | | | |
| 400/1 | 05 | 15 | | | |
| 500/1 | 05 | 25 | | | |

| 600/1 | Column 2 | 05 | Column 4 | 25 |
|---|---|---|---|---|
| 750/1 | 05 | 25 | | |
| 800/1 | 05 | 25 | | |
| 1000/1 | 05 | 5 | | |

开合式XH 型互感器 XH-80*50 Split Core Current Transformer 一、SPECIFICATIONS： 1、Standard ： GB1208 and IEC60044-1; 2、Rated Frequency：0.66KV; 3、Operating Temperature：-15℃to 45℃; 4、Certificates：CE 二、FEATURES： Open type current transformer standard is mainly used in industrial city network,rural power network reconstruction project. The installation is convenient. They may be installed without opening any cable or bus-bar circuit. It does not affect thenormal use of electricity customers, save a lot of manpower, material resources,financial resources , Improve the efficiency of transformation. 三、DIMENSIONS( mm )： 四、PARAMETERS： 1、Output:5A Model Ratio（A） Accuracy Burden（VA） Frequency XH-80*50 1 1.5 50/60Hz ≤3KV 1 1.5 0.5 1.5 0.5 2.5 0.5 2.5 0.5 2.5 0.5 2.5 0.5 5 2、Output:1A Model

**地址 ADD.:** No.3399, Luzhou Ave., Baohe Dist., Hefei, Anhui 230051, China | 安徽省合肥市包河区庐州大道3399号
**传真 Fax:** +0086-551-64683490 **营业执照注册号 Business License Reg. No.:** 91340100575703313N
**海关注册编码 Customs Reg. Code:** 3401961393

**ASIA PACIFIC INDUSTRY GROUP CO., LIMITED**
Tel +0086-551-64687285
Email sales@boppfilmsales.com
www.boppfilmsales.com · www.apigcl.com

以下数据为本产品技术规格，随货签发检验记录。

Ratio（A） Accuracy Burden（VA） Frequency XH-80*50 1 1.5 50/60Hz ≤3KV 1 1.5 0.5 1.5 0.5 2.5 开合式XH型互感器 0.5 2.5 0.5 2.5 0.5 2.5 0.5 5

## 3 • NOTES 说明

This document states the standard specification of the product. Values apply to the grades listed here; the tolerance range agreed in the order confirmation and the technical agreement prevails for any specific order. Batch test records are issued with the goods on request.