ASIA PACIFIC INDUSTRY GROUP CO., LIMITED
Tel +0086-551-64687285
Email sales@boppfilmsales.com
www.boppfilmsales.com · www.apigcl.com

Self-Adhesive Tear Tape — Product Test Report

PE 薄膜 — 检测数据

Document No. 文件编号	Revision 版本	Issue date 签发日期	Document type 文件类型
APIG-TDS-TEARTAPE-2026	**Rev. 2.0**	**2026-11-09**	**Test Data / 检测数据**

1 • DOCUMENT INFORMATION 文档信息

Item 项目	Description 说明
Document type 文件类型	Test Data / 检测数据
Subject 主题	Self-Adhesive Tear Tape — Product Test Report
Specification basis 规格依据	APIG product specification 亚太工业集团产品规格
Issue 签发	2026-11-09 · Rev. 2.0
Language 语言	Bilingual headings — English / 中文

2 • TECHNICAL CONTENT 技术内容

Tear Tape Product Test	Column 2	Column 3	Column 4	Column 5	Column 6	Column 7
quantity						
testindicators						realvalue dat
20±01						20
≥13						136
≤170						1523
≥012						07
≥30						60
Qualified						
satisfy						Qualified

Exterio r	surface	Column 3	Surfacesmooth uniformcolor , , flu	satisfy	Qualified
Solid nodistortion nodents , , , nicks					
Core	looseandintotheend	satisfy	Qualified		
face Itsho					
Clearandcompletepri nted pattern position					
surface	sizeratiowith	satisfy	Qualified		
thedesignre					
Handwriting lines symbols					

地址 ADD.: No.3399, Luzhou Ave., Baohe Dist., Hefei, Anhui 230051, China | 安徽省合肥市包河区庐州大道3399号
传真 Fax: +0086-551-64683490 **营业执照注册号 Business License Reg. No.:** 91340100575703313N
海关注册编码 Customs Reg. Code: 3401961393

ASIA PACIFIC INDUSTRY GROUP CO., LIMITED
Tel +0086-551-64687285
Email sales@boppfilmsales.com
www.boppfilmsales.com · www.apigcl.com

Exterio r	surface	Column 3	Surfacesmooth uniformcolor , , flu	satisfy	Qualified
Pattern printin g	clearandfull centered	satisfy	Qualified		
finaldecision	Qualified				

Tear Tape Product Test Report Manufacturer: Asia Pacific Industry Group Co., Limited Commodity Self Adhesive Tear Tape quantity Standard Q/SZ 104 017-2018 Standards measured Unit test indicators real value data judgment Width mm 2.0±0.1 2.0 Qualified Tensile strength N/2.5m m ≥13 13.6 Qualified Elongation at break % ≤170 152.3 Qualified 180 ° peel strength N/cm ≥0.12 0.7 Qualified Holding adhesive min ≥30 60 Qualified Winding way - A/B - Qualified Adhesi ve layer -- Rubber face, the layer uniform, transparent and clear, no dust and impurities. satisfy Qualified · Exterio r surface -- Surface smooth, uniform color, flush on both sides, no creases, excess glue, stain, when unwinding non-adhesive surface without adhesive residue. satisfy Qualified Core -- Solid, no distortion, no dents, nicks, loose and into the end face. It should be wound neatly, no scratches, no edges, no dislocation. satisfy Qualified surface -- Clear and complete printed pattern, position, size ratio with the design requirements, no color. satisfy Qualified Pattern printin g -- Handwriting, lines, symbols, clear and full, centered. satisfy Qualified final decision Qualified ·

以下数据为本产品技术规格，随货签发检验记录。

3 • NOTES 说明

This document states the standard specification of the product. Values apply to the grades listed here; the tolerance range agreed in the order confirmation and the technical agreement prevails for any specific order. Batch test records are issued with the goods on request.